

D&B 35-MULTI

Purposely designed for the Australian drilling industry and Australian conditions.

The most popular model in the D&B range, with units sold and working in Africa, the Philippines, South America and all over Europe.

Mounted on a larger track base, with more horsepower than the 30-Multi, the 35-Multi is an impressive rig that will cover almost all of your clients' requirements.

STANDARD SPECIFICATIONS

MAIN WINCH	17,000 kg
RETRACT FORCE	30,000kg
RETRACT SPEED	30m/min
PULL DOWN FORCE	18,000kg
PULL DOWN SPEED	35m/min
HEAD STROKE	7m
HP	280/ 350/ 540
ENGINE	Doosan DL08/ Hyundai D6CC
ROTATION SPEED	1100 rpm

*DEPTH CAPABILITY

PWL (114.3mm)	Up to 500m
HWL (88.9mm)	Up to 1,200m
NWL (69.9mm)	Up to 2,000m
BWL (55.6mm)	Up to 2,500m

BASIC RIG DIMENSIONS

OA LENGTH	12.1M
OA WIDTH	2.6M
OA TRANSPORT HEIGHT	3.2M
HEIGHT (MAST RAISED VERTICALLY)	12M
DRY WEIGHT (DEPENDING)	17.25T

EXTENDABLE
JIB CRANE
ARM - 520kg

MANUAL AND
TABLE MOUNTED
BREAKOUT
SYSTEMS



STANDARD EQUIPMENT

WIRELESS REMOTE
CONTROL FOR TRAVEL
1100 MAX ROTATION
SPEED
6M DRILL PIPE CAPACITY
TWIN HEAD ROTATION
RISK ASSESMENT
ADJUSTABLE CONTROL
PANEL
HYDRAULICS HOSE
COVERINGS
SAFETY CAGE
HYDRAULICS FOOT
CLAMPS
P,H,N JAWS

OPTIONAL EXTRAS

UP TO 1500 LPM MUD
PUMP
1070CFM ON BOARD
COMPRESSOR
AMERICAN TRIPLEX
PISTON PUMP
ROD LOADER
WIRELINE ARCHIMEDES
GUIDE

*Under normal drilling conditions

**DISCOVER OUR
CAPABILITIES**

Call: +61 3 5445 6900
Email: sales@mccullochs.com.au
Visit: mccullochsdriilling.com



McCULLOCHS
DRILLING & BORING

